

FLY-1801

iNetVu®
by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

The iNetVu® FLY-1801 Antenna is a 1.8m highly portable, self-pointing, auto-acquire unit that is configurable with the iNetVu® 7710 Controller and can be assembled in less than 20 minutes. The antenna features a 6-piece carbon fibre reflector with compact pedestal and is designed to be cost-effective while providing exceptional performance in a light weight package.



Features

- 6-Piece Carbon Fibre Reflector
- One button, auto-pointing Controller acquires any Ku or C band satellite within 2 minutes
- 3 Axis motorization
- Supports manual control
- Captive Hardware/Fasteners
- No tools required for assembly
- Set-up time less than 20 minutes
- Designed to work with the iNetVu® 7710 Controller
- Leveling capability for uneven surfaces
- Standard 2 year warranty



Application Versatility

Whether you operate in Ku or C band, the 1.8m Flyaway system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. Ideally suited for industries such as Disaster Management, Military, Oil & Gas Exploration, Mining, Construction, Mobile Offices and Emergency Services.

C-COM
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)
www.c-comsat.com

Specifications are subject to change

Dec 2018

FLY-1801

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

Mechanical

Reflector	1.8m offset feed, Carbon Fibre
Platform Geometry	Elevation over Azimuth
Deployment Sensors GPS Antenna	Compass ± 2°, Tilt Sensor ± 0.2°
F/D Ratio	0.80
Azimuth	Full 360° in overlapping, 200° sectors
Elevation	0° to 90°
Polarization	± 95°
Elevation Deploy Speed	Variable 3° /sec, 2° /sec typ.
Azimuth Deploy Speed	Variable 5° /sec, 2° /sec typ.
Peaking Speed	0.2° /sec
Peaking Accuracy	±0.1°
Motor Voltage	24VDC 15 Amp (Max.)

Environmental

Wind loading	
Operational (no ballast)	40 km/h (25 mph)
Operational (with ballast)	72 km/h (45 mph)
Survival (with ballast)	120 km/h (75 mph)
Temperature	
Operational	-30° to 60° C (-22° to 140° F)
Survival	-40° to 65° C (-40° to 149° F)
Water Ingress Rating	IP-66

Electrical

Rx & Tx Cables	2 RG6 Cables
Control Cables	
Standard	10 m (33 ft) Extension Cable
Optional	Up to 60 m (200 ft) available

RF Interface

Radio Mounting	Feed arm
Coaxial	RG6U
Axis Transition	Rigid/Twist-Flex Waveguide
Electrical Interface	10 m (33 ft) ext. cables w/MIL connectors
VSWR	Rx 1.30:1 Tx 1.30:1

Physical

Transportable Cases:

- Case 1: AZ Assembly: 47.7 x 50.8 x 68.6cm (18.8" x 20" x 27"); 40.2kg (89lbs)
 - Case 2: Tripod Assembly: 52.1 x 154.5 x 34.3cm (20.5" x 61" x 13.5"); 36.4kg (80lbs)
 - Case 3: EL Assembly & Feedboom Supports: 49.5 x 138.5 x 67.3cm (19.5" x 54.5" x 26.5"); 39.6kg (87.5lbs)
 - Case 4: Feedboom Assembly & Reflector segments: 55.9 x 98.6 x 68.6cm (22" x 38.8" x 27"); 39.6kg (87.5lbs)
 - Case 5: Controller (Optional): 4-10U Rack Mount : 74 x 51 x 72 cm (29" x 20" x 28"); 32 kg (70 lbs)
- Climate Control case also available

Optional Feeds:

- Case 6: Ku-Linear POL & EL Actuator: 69.9 x 770 x 351cm (27.5" x 30.3" x 13.8"); 32.5kg (71.5lbs)
- Case 7: C-linear POL & EL Actuator: 75 x 75 x 48.3cm (29.5" x 29.5" x 19"); 46.2kg (102lbs)
- Case 8: C-Circular POL & Actuator: TBD

Ku-Band (Linear Orthogonal)

	Receive	Transmit
Transmit Power ⁽¹⁾	1 to 200 watt	
Frequency (GHz)	10.70-12.75 ⁽²⁾	13.75-14.50
Feed Interface	WR75	WR75
Efficiency	70%	70%
Midband Gain (± 0.2dBi)	45.30	46.50
Antenna Noise Temp. (K)	10° EL= 60 / 20° EL= 53	
Sidelobe Envelope,	1°<θ<20°	29-25 Log θ
Co-Pol (dBi)	20°<θ<26.3°	-3.5
	26.3°<θ<48°	32-25 Log θ
	48°<θ<180°	-10 (Average)
Cross-Polarization on Axis	-35 dB	-35 dB
Within 1dB Beamwidth	-28 dB	-28 dB
Isolation (Port to Port)	30 dB	85 dB

C-Band (Linear)

	Receive	Transmit
Standard Frequency (GHz)	3.40-4.20 ⁽²⁾	5.850-6.725
INSAT Frequency (GHz)	4.50-4.80 ⁽²⁾	6.725-7.025
Feed Interface	WR229	WR137 or Type N
Midband Gain (± 0.3 dBi)	35.40	39.30
Antenna Noise Temp. (K)	10° EL= 43 / 20° EL= 38	
Sidelobe Envelope,	2.5°<θ<20	29-25 Log θ
Co-Pol (dBi)	20°<θ<26.3°	-3.5
	26.3°<θ<48°	32-25 Log θ
	48°<θ<180°	10 (Average)
Cross-Pol: on Axis	-30 dB	-30 dB
Within 1dB Beamwidth	-26 dB	-26 dB
Isolation (Port to Port)	30 dB	70 dB

C-Band (Circular)

	Receive	Transmit
Standard Frequency (GHz)	3.625-4.20 ⁽²⁾	5.85-6.425
Feed Interface	WR229	Type N
Midband Gain (± 0.4dBi)	35.4	39.50
Antenna Noise Temp. (K)	10° EL= 55 / 20° EL= 50	
Sidelobe Envelope,	2.8°<θ<20°	29-25 Log θ
Co-Pol (dBi)	20°<θ<26.3°	-3.5
	26.3°<θ<48°	32-25 Log θ
	48°<θ<180°	-10 (Average)
Isolation (Port to Port)	30 dB	70 dB

Shipping Weights & Dimensions

TBD

Notes:

- ⁽¹⁾ Depending on size and weight of feed arm mounting limitation
- ⁽²⁾ LNB PLL Type required with stability better than ± 25 KHz

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)
www.c-comsat.com

Please note this is a draft.
Specifications are subject to change

Dec 2018